# **Specifying Joint Sealants: Selection & Design Considerations**



### **Formal CPD Activity Questions**

#### 1. Identify 5 correct functions of a joint sealant:

- A. Absorb movement of building materials
- B. Minimize sound transmission
- C. Allow moisture to penetrate a joint
- D. Waterproofing / weather seal
- E. Aesthetic / architectural sealing
- F. Inhibit movement of adjacent materials
- G. Prevent spread of smoke/fire
- H. Transfer sound to internal spaces

## 2. A 20mm joint has been designed to accommodate 5mm expansion and 5mm compression. What minimum movement capability does the sealant require?

- A. 10% or ±5% minimum movement capability
- B. 50% or ±25% minimum movement capability

#### 3. True or false:

When sealing a dynamic joint, the use of a backing rod or bond breaker tape is optional

- A. True
- B. False

#### 4. When should a joint be primed?

- A Prime all joints with the appropriate primer as recommended by the sealant manufacturer.
- B Only external joints require priming

#### 5. True or false:

In a building of Type A or B Construction, joint sealants used in external wall assemblies are required to be non-combustible?

- A. True
- B. False





# **Specifying Joint Sealants: Selection & Design Considerations**



### **Formal CPD Activity Questions**

- 6. Which of the following sealant technologies are paintable after full cure has been achieved?
  - A. Acrylics
  - B. Polyurethanes
  - C. Silicones
  - D. Hybrids
- 7. What is sealant staining and how can it be avoided?
  - A Sealant staining occurs when excess sealant is smeared onto adjacent surfaces during installation. It can be avoided by taping either side of the joint prior to application of the sealant.
  - B Sealant staining occurs when non-reacted plasticizers, solvents or fluids leach out of the sealant and into adjacent surfaces creating a wet look. It can be avoided by selecting products that do not contain plasticizers, are not diluted and by compatibility prior to application.

Name:		

Please email completed answers to <u>specification.au@bostik.com</u> to receive your personalised record of completion for your CPD log.



